

**Type designation: KETO-00-3/F**

**Article number: T500113002**

### Images



(Illustration similar)

### Description

according to EN60947-3, size NH00 - 160A, 3pole  
for baseplate mounting  
with universal terminal M8 x 16/2 x M5  
cable terminal at top and bottom side  
new design (black switching handle)

### Features

Type:	KETO-00-3/F
Product Lifecycle:	Active product
Product standard:	IEC/DIN EN60947-3
Size:	NH00
Rated operating voltage $U_e$ :	690 V
Rated operating current $I_e$ :	160 A
Conv. free air thermal current with fuse-links $I_{th}$ :	160 A
Conv. free air thermal current with solid links:	250 A
Rated frequency:	50 - 60 Hz
Rated isolation voltage $U_i$ :	1,000 V
Total power loss at $I_{th}$ (without fuse-link) $P_V$ :	9 W
Power loss at 80% $I_{th}$ (without fuse-link):	5.8 W
Utilization category 1:	690V - 160A - AC-21B
Utilization category 2:	400V - 160A - AC-23B
Utilization category 3:	250V - 160A - DC-22B
Rated impulse voltage $U_{imp}$ :	8 kV
Rated conditional short-circuit current $I_{cc}$ :	120 (AC 500V) kA
Rated short-time withstand current (kA):	5
Max. permissible power dissipation per fuse-link:	12 W
Ambient temperature:	-25 up to +70 (Attention derating of rated current required) °C
Altitude:	2000 m
Pollution degree:	3
Overvoltage category:	III
Mounting position:	vertical / horizontal
Electrical endurance (switching cycles):	200
Mechanical endurance (total switching cycles):	1,600
Material properties:	<b>Unterteil:</b> Temperaturbeständigkeit bis 125°C Selbstverlöschend nach UL94 Kriechstromfestigkeit CTI 600 Halogenfrei

**Schutzabdeckungen, Schaltdeckel:**

Temperaturbeständigkeit bis 125°C  
 Selbstverlöschend nach UL94  
 Kriechstromfestigkeit CTI 600  
 Halogenfrei

**Sicherungsaufnahmekontakte:**














E-Cu, versilbert, fremdbefedert

Degree of protection:	IP2XC
Applicable for fuse-links:	NH000, NH00
Cable terminal:	Universal terminal M8 / 2 x M5
Direction of cable terminal:	variable
Type of installation:	Baseplate mounting
Poles:	3
Fuse monitoring:	None
Hight:	195 mm
Width:	106 mm
Depth:	84 mm
ETIM - Code:	EC001040

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 05.03.2024 / 08:46

**Documents**

	Catalogue	
	Dimensions	
	Operating manual	
	3D-STEP	
	Rated diversity factor	
	Catalogue Appendix	
	CE-conformity declaration	