

**Type designation: RS-60/273-5**

**Article number: G1723005**

## Images



(Illustration similar)

## Description

Busbar mounting DII / DIII-fuse-bases for 60mm busbar system

## Features

Type:	RS-60/273-5
Product standard:	IEC/EN 60269
Size:	DII
Rated operating voltage $U_e$ :	500 V
Rated operating current $I_e$ :	25 A
Rated current:	25 A
Conv. free air thermal current with fuse-links $I_{th}$ :	25 A
Rated frequency:	50 - 60 Hz
Total power loss at $I_{th}$ (without fuse-link) $P_V$ :	1.5 W
Max. permissible power dissipation per fuse-link:	4 W
Ambient temperature:	-25 up to +55 (≥35 derating of rated current required) °C
Duty type:	Continuous duty
Altitude:	2000 m
Pollution degree:	3
Overvoltage category:	III
Mounting position:	vertical / horizontal
Degree of protection:	IP20
Applicable for fuse-links:	DII
Thread:	E27
Cable terminal:	Elevator clamp F25 0,75-25mm <sup>2</sup>
Busbar distance:	60 mm
busbar thickness:	<ul style="list-style-type: none"> <li>• 5</li> <li>• 10</li> </ul> mm
Busbar width:	<ul style="list-style-type: none"> <li>• 12</li> <li>• 20</li> <li>• 30</li> </ul> mm
Poles:	3
Width:	45 mm

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 25.03.2024 / 10:43

## Documents



Catalogue



Operating manual



Rated diversity factor



Catalogue Appendix



CE-conformity declaration

