

## Type designation: AM-60/250/3

Article number: G1540000

### Images



(Illustration similar)

### Description

Anschlussmodul Typ AM-60/250/3,  
für 60mm-, 3polig- Sammelschienensysteme, Bemessungsbetriebsstrom 250A  
Fahrstuhlklemme F70 1,5-70mm<sup>2</sup> Cu

### Features

Type:	AM-60/250/3
Rated operating voltage $U_e$ :	690 V
Rated operating current $I_e$ :	250 A
Rated frequency:	50 - 60 Hz
Rated isolation voltage $U_i$ :	690 V
Total power loss at $I_{th}$ (without fuse-link) $P_V$ :	6.5 W
Cable terminal:	Elevator clamp F70 1,5-70mm <sup>2</sup> Cu
Cross-section copper round solid:	1,5-16 mm <sup>2</sup>
Cross-section copper sector solid:	/ mm <sup>2</sup>
Cross-section copper sector stranded:	35-70 mm <sup>2</sup>
Busbar distance:	60 mm
busbar thickness:	<ul style="list-style-type: none"> <li>• 5</li> <li>• 10</li> </ul> mm
Busbar width:	<ul style="list-style-type: none"> <li>• 20</li> <li>• 30</li> </ul> mm
Poles:	3
Width:	54 mm

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 25.03.2024 / 13:50

### Documents



Catalogue



Operating manual



Rated diversity factor





Catalogue Appendix



CE-conformity declaration

