

Type designation: U2-3IGZ/H

Article number: U2311308

Images



(Illustration similar)

Description

NH fuse-bases for baseplate mounting size 1-3 AC690V

Features

Type:	U2-3IGZ/H
Product standard:	IEC/EN 60269
Applicable for fuse-links:	NH2
Rated operating voltage U_e :	690 V
Rated operating current I_e :	400 A
Conv. free air thermal current with fuse-links I_{th} :	400 A
Conv. free air thermal current with solid links:	520 A
Rated frequency:	50 - 60 Hz
Rated isolation voltage U_i :	1,000 V
Altitude:	2000 m
Max. permissible power dissipation per fuse-link:	45 W
Ambient temperature:	-25 up to +70 (Attention derating of rated current required) °C
Duty type:	Continuous duty
Pollution degree:	3
Overvoltage category:	III
Mounting position:	vertical / horizontal
Protective cover:	true
Cable terminal:	Flat terminal M10
Poles:	3

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 25.03.2024 / 15:25

Documents



Catalogue



Operating manual





Dimensions



Drilling template



Catalogue Appendix



CE-conformity declaration

