

Type designation: K4G/3

Article number: K4203002

Images



(Illustration similar)

Description

Steel-frame clamp for devices with falt terminal lug for up to 3 wires connection

Features

Type:	K4G/3
max. clamping range:	50 - 300 mm ²
Cross-section copper round solid:	<ul style="list-style-type: none"> • 1x50-50 • 2x50-50 • 3x50-50 mm ²
Cross-section copper round stranded:	<ul style="list-style-type: none"> • 1x50-300 • 2x50-240 • 3x50-185 mm ²
Cross-section copper sector solid:	<ul style="list-style-type: none"> • 1x70-185 • 2x70-185 • 3x70-185 mm ²
Cross-section copper sector stranded:	<ul style="list-style-type: none"> • 1x70-300 • 2x70-185 • 3x70-185 mm ²
Cross-section aluminium round solid:	<ul style="list-style-type: none"> • 1x50-50 • 2x50-50 • 3x50-50 mm ²
Cross-section aluminium round stranded:	<ul style="list-style-type: none"> • 1x50-300 • 2x50-240 • 3x50-185 mm ²
Cross-section aluminium sector solid:	<ul style="list-style-type: none"> • 1x70-185 • 2x70-185 • 3x70-185 mm ²
Cross-section aluminium sector stranded:	<ul style="list-style-type: none"> • 1x70-300 • 2x70-185 • 3x70-185 mm ²
Nominal torque:	50 Nm
Gültigkeit Querschnitt:	Cross section valid for thickness of terminal lug 3-10mm
Packaging unit:	1

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 26.03.2024 / 09:38

Documents



Catalogue




Catalogue Appendix



CE-conformity declaration



Drawings



(Illustration similar)